



Description:

The ThermaData logger is a cost effective, self-contained temperature data-logger or blind recording thermometer that is designed to record the temperature of the surrounding environment. The ThermaData logger is housed in a water-resistant polyethylene case and incorporates two LED status indicators.

Features:

- * Software allows the user to programme the logging sample/interval rate (1 to 255 minutes), the real-time clock, °C or °F, delayed start (maximum 23 hours, 59 minutes) or push-button start and a 12-character user ID

- * It also incorporates a password protected calibration adjustment feature that checks the calibration of loggers and makes minor adjustments 0.5 °C (±3 °C)

- * ThermaData logger will continue recording during and after downloading the data unlike most low cost loggers

- * User can also set within the software, high and low alarm values for a specific application

- * 3 blind recording thermometer & data-logger

- * 3 visual display of high & low alarm status

- * 3 range -40 to 85 °C

- * 3 simple visual inspection shows if limits exceeded

| | |
|-----------------------|--|
| Technical Date | ETI-293001 |
| Range | -40 to 85 °C |
| Resolution | ±1 °C (±0.5 °C with calibration utility) |
| Accuracy | 2048 temperature readings |
| Memory | 1 minute to 255 minutes |
| Sample Rate | 3.6 volt ½ AA lithium |
| Battery | 3 years |
| Battery Life Minimum | Ø55 x 25 mm |
| Weight | 45g |